

Surgical Tissue Management System Electrosurgical Generator **ESG-400**



Electrosurgical Generator

ESG-400



ESG-400 Features and Benefits

Full range of monopolar and bipolar modes	<ul style="list-style-type: none"> Perform open, lap and endoscopic surgery procedures
Tissue-adaptive power output	<ul style="list-style-type: none"> Apply the optimal amount of energy Controlled, precise and quick cutting
Touch screen	<ul style="list-style-type: none"> Choose settings easily
Quick memory function	<ul style="list-style-type: none"> Find your preferred settings easily
Instrument recognition	<ul style="list-style-type: none"> Plug & Play at the Olympus UNIVERSAL socket
New saline modes (for bipolar resection)	<ul style="list-style-type: none"> Improved ignition performance Continuous vaporization
Saline detection	<ul style="list-style-type: none"> Make sure that you are using the right fluid
Compatibility with Olympus equipment:	
- USG-400	<ul style="list-style-type: none"> THUNDERBEAT instrument
- ENDOALPHA	<ul style="list-style-type: none"> OR integration
- UHI	<ul style="list-style-type: none"> Automatic smoke evacuation

ESG-400 Technical Specifications

Power supply

Voltage range	100 to 120 V- / 220 to 240 V-
Frequency	50/60 Hz
Maximum input power	1500 VA
Power fuse	10 A (only FST-series from Schurter)
Terminal for potential equalization	Yes

Output

High frequency functions	Monopolar/Bipolar
High frequency	430 kHz \pm 20%
Maximum high frequency power	320 W
All modes	25% duty cycle
RFCoag (with or without RCAP)	100% duty cycle

Classification

Protection class according to IEC 60601-1	CF, Class I
Classification according to MDD 93/42/EEC	IIb

Sockets

MONOPOLAR	2 x 3-pin (\varnothing 4 mm), International standard 1 x 1-pin (\varnothing 8 mm), Bovie standard 1 x coaxial (\varnothing inner 5 mm / \varnothing outer 9 mm), Erbe standard
BIPOLAR	1 x 2-pin (\varnothing 4 mm, pin spacing 28.8 mm), International standard 1 x coaxial (\varnothing inner 4 mm / \varnothing outer 8 mm), Erbe standard
UNIVERSAL	1 x 7-pin, Olympus standard
Neutral electrode	2-pin standard, single or split

Size and weight

Width x Depth x Height	370 x 465 x 156 mm
Weight	12.5 kg

Operation environment

Temperature	10 to 40 °C (50 to 104 °F)
Relative humidity	30 to 85%, non-condensing
Atmospheric pressure	70 to 106 kPa

Output characteristics

	Mode	Maximum output voltage [Vp]	Maximum power level [W]
MONOPOLAR	CUT	PureCut	740
		BlendCut	1400
		PulseCut slow	800
	COAG	PulseCut fast	800
		SoftCoag	220
		PowerCoag	2500
BIPOLAR	CUT	ForcedCoag	2000
		SprayCoag	4300
		BipolarCut	700
		SalineCut	700
	COAG	BiSoftCoag	220
		AutoCoag	220
		SalineCoag	230
		HardCoag	220
	RFCoag	220	
	FineCoag	220	

Order information

Article	Article number	Additional information
ESG-400 electrosurgical generator*	WB91051W	
Footswitch double pedal	WB50402W	
Footswitch single pedal	WB50403W	
Power cable, EU, 4.5 m, with angled plug	WA95621A	Many European countries, Type E/F
Power cable, US, 4.5 m, with angled plug	WA95622A	USA, Canada and other countries, Type B
Power cable, UK, 4.5 m, with angled plug	WA95623A	United Kingdom and other countries, Type G
ESG-400 SALINE cable	WA00014A	
Energy cart	TC-E400	
Neutral electrode cable (reusable)	MAJ-814	

* Including one double footswitch.

OLYMPUS

Published by
OLYMPUS SURGICAL TECHNOLOGIES EUROPE
 Olympus Winter & Ibe GmbH, Kuehnstraße 61, 22045 Hamburg, Germany

For a complete listing of
 sales and distribution locations visit:
www.olympus.com